

1

For each question **Q1 - Q4** below answer what is printed by the commented line on your answer sheet. If a runtime or compile time error, answer "Err". If the statement is legal and nothing is printed, answer "Ok".

```
class A {  
private:  
    virtual void p( );  
protected:  
    virtual void q( );  
public:  
    virtual void r( );  
};  
  
void A::p( ) {cout << "A::p" << endl;};  
void A::q( ) {cout << "A::q" << endl;};  
void A::r( ) {cout << "A::r" << endl;};
```

```
class B : protected A {
```

```
public:  
    void foo( );  
};
```

```
void B::foo( ) {  
    q( );  
    r( );  
}
```

```
int main( ) {
```

```
    A a;  
    B b;
```

```
    a.q( ); // Q1  
    a.r( ); // Q2
```

```
    b.q( ); // Q3  
    b.r( ); // Q4
```

```
}
```

For each question **Q5 - Q11** below answer what is printed by the commented line on your answer sheet. If a runtime or compile time error, answer "Err". If the statement is legal and nothing is printed, answer "Ok". For **Q8** and **Q11**, say what is printed by both lines, or "Err" if either line is illegal or produces an error.

```

class Base {
public:
    Base( );
    virtual ~Base( );
};

Base::Base( ) {}
Base::~~Base( ) {}

class A : public Base {
public:
    virtual void p( );
    virtual void q( );
};

void A::p( ) {cout << "A::p" << endl;}
void A::q( ) {cout << "A::q" << endl;}

class B : public Base {
public:
    virtual void q( );
    virtual void r( );
};

void B::q( ) {cout << "B::q" << endl;}
void B::r( ) {cout << "B::r" << endl;}

int main( ) {
    Base* baseP = new A( ); // Q5
    A* aP = new A( );
    B* bP = new B( );

    baseP = aP; // Q6
    aP = static_cast<A*>(bP); // Q7
    aP = dynamic_cast<A*>(bP);
    aP->q( ); // Q8

    aP = baseP; // Q9
    aP = static_cast<A*>(baseP); // Q10
    aP = dynamic_cast<A*>(baseP); // Q11
    aP->p( ); // Q11:w
}

```

3

For each question **Q12 - Q16** below answer what is printed by the commented line on your answer sheet. If a runtime or compile time error, answer "Err". If the statement is legal and nothing is printed, answer "Ok".

```
class A {
```

```
public:
```

```
    A( );
```

```
    A(int);
```

```
    virtual ~A( );
```

```
    virtual void f(A*);
```

```
    int i;
```

```
};
```

```
A::A( ) : i(-1) {cout << "A0" << endl; i = -2;}
```

```
A::A(int k) {cout << "A1" << endl; i = k;}
```

```
A::~~A( ) {cout << "A-" << endl;}
```

```
void A::f(A* p) {cout << (p == this) << endl;}
```

```
class B : public A {
```

```
public:
```

```
    B( );
```

```
    B(int, int);
```

```
    virtual ~B( );
```

```
    int k;
```

```
    int j;
```

```
};
```

```
B::B( ) : j(0), k(0) {cout << "B0" << endl;}
```

```
B::B(int m, int n) : j(5), k(j), A(1) {cout << "B1" << endl;}
```

```
B::~~B( ) {cout << "B-" << endl;}
```

```
int main( ) {
```

```
    b0;
```

```
    b1(2, 3); // Q12
```

```
    std::cout << b0.i << " " << b0.j << " " << b0.k << std::endl; // Q13
```

```
    std::cout << b1.i << " " << b1.j << " " << b1.k << std::endl; // Q14
```

```
    B* p = &b0;
```

```
    p->f(p); // Q15
```

```
} // Q16, what if anything is printed when main is exited?
```

For each question **Q17 - Q28** below answer what is printed by the commented line on your answer sheet. If a runtime or compile time error, answer “Err”. If the statement is legal and nothing is printed, answer “Ok”.

```
class A {
public:
    A();
    int i;
};

A::A() : i(-1) {}
```

```
// main.cpp
void f1(A ap) {
    ap.i = 0;
}

void f2(A& ap) {
    ap.i = 1;
}

void f3(A* ap) {
    ap->i = 2;
}

int main( ) {
    A a;
    A* aP = &a;
    A& aR = a;

    f1(a);
    std::cout << a.i << std::endl; // Q17
    f1(aP);
    std::cout << a.i << std::endl; // Q18
    f1(aR);
    std::cout << a.i << std::endl; // Q19

    f2(a); // Q20
    std::cout << a.i << std::endl; // Q21
    f2(aP); // Q22
    std::cout << a.i << std::endl; // Q23
    f2(aR); // Q24
    std::cout << a.i << std::endl; // Q25

    f3(a);
    std::cout << a.i << std::endl; // Q26
    f3(aP);
    std::cout << a.i << std::endl; // Q27
    f3(aR);
    std::cout << a.i << std::endl; // Q28
}
```

For each question **Q29 - Q50** below answer what is printed by the commented line on your answer sheet. If a runtime or compile time error, answer "Err". If the statement is legal and nothing is printed, answer "Ok".

```

class A {
private:
    virtual void p();

public:
    A();
    virtual void q();
    virtual void r();
    void s();
    void t();
    int i;
    int j;
private:
    virtual void u();
};

A::A() {i = 1; j = 2;};

void A::p() {cout << "A::p" << endl;}
void A::q() {cout << "A::q" << endl;}
void A::r() {cout << "A::r" << endl;}
void A::s() {cout << "A::s" << endl; u();}
void A::t() {cout << "A::t" << endl;}
void A::u() {cout << "A::u" << endl;}

class B : public A {

public:
    B();
    void q();
    void r();
    virtual void s();
    void t();
    int j;
};

B::B() : A() {j=3;};
void B::q() {cout << "B::q" << endl;}
void B::r() {cout << "B::r" << endl;}
void B::s() {cout << "B::s" << endl;}
void B::t() {cout << "B::t" << endl;}

```

```

class C : public B {
public:
    C();
    virtual void s();
    void t();
    int j;
};

C::C() : B() {j=4;};
void C::s() {cout << "C::s" << endl;}
void C::t() {cout << "C::t" << endl;}

int main() {
    A a;
    B b;
    C c;

    A& aR = b;
    B& bR = c;
    A* aP = &b;
    B* bP = &c;

    aR.q(); // Q29
    aR.s(); // Q30
    aR.t(); // Q31
    bR.r(); // Q32
    bR.s(); // Q33
    bR.t(); // Q34

    aP->q(); // Q35
    aP->r(); // Q36
    aP->s(); // Q37
    aP->t(); // Q38
    bP->q(); // Q39
    bP->r(); // Q40
    bP->s(); // Q41
    bP->t(); // Q42

    a = c;
    a.q(); // Q43
    a.r(); // Q44
    a.s(); // Q45
    a.t(); // Q46
    std::cout << aP->i << std::endl; // Q47
    std::cout << aP->j << std::endl; // Q48
    std::cout << bP->i << std::endl; // Q49
    std::cout << bP->j << std::endl; // Q50
}

```